



NWA50BE

BE5100 4-Stream WiFi 7 Dual-Radio NebulaFlex Access Point

The Zyxel NWA50BE is a WiFi 7 access point designed to provide an ideal feature set for small businesses, SoHo users, and small spaces seeking an affordable upgrade to WiFi 7. Built for home offices, compact workplaces, and homes, it offers an effortless path to WiFi 7 with faster speeds and reliable, wide-area coverage.

Powered by a Qualcomm quad-core CPU, the BE5100 (2.4GHz: 2x2:2, 5GHz: 2x2:2) dual-radio access point delivers ultra-fast WiFi 7 speeds of up to 5.1Gbps, ensuring enterprise-grade performance in a compact design. Its 2.5GbE uplink unlocks the full potential of WiFi 7 for high-speed connectivity.

With a straightforward setup via Nebula Cloud Networking, you can quickly configure the access point, set up separate networks for work and family use, and start enjoying ultra-fast WiFi 7 speeds.

Smart Mesh MLO technology automatically establishes dynamic wireless links, eliminating the need for complex, inconvenient cabling in WiFi deployments. Unlike traditional mesh networks that rely on a single radio for data transmission, the NWA50BE utilizes dual-radio backhaul, delivering superior bandwidth, enhanced interference resistance, and ultra-low latency for seamless, high-performance connectivity.

Featuring NebulaFlex, the NWA50BE offers flexible management options, allowing you to choose between standalone, local GUI management or the intuitive Nebula Cloud management interface. With Nebula, users can enjoy hassle-free cloud networking without the need to remember IP addresses or passwords.



BE5100 (2.4GHz: 2x2:2, 5GHz: 2x2:2) dual-radio access point offers blazingly fast WiFi 7 speeds of up to 5.1Gbps, ensuring lower latency for real-time responsiveness



Smart Mesh MLO with dual-radio backhaul enables dynamic, cable-free deployment while delivering higher bandwidth, lower latency, and stronger interference resistance



The 2.5GbE port offers a cost-effective boost beyond gigabit, enabling WiFi 7 performance while staying compatible with existing infrastructure



NebulaFlex allows users to switch between standalone or intuitive Nebula cloud managed modes as needed

Benefits

Bringing next generation WiFi within reach

WiFi 7, also known as IEEE 802.11be, represents the next evolution in WiFi standards, supporting all three frequency bands – 2.4GHz, 5GHz, and 6GHz. With its revolutionary technological advancements, it promises to redefine the concept of speed, delivering unprecedented rates to elevate online experiences in the digital realm.

Powered by a Qualcomm quad-core CPU, the NWA50BE access point provides ultra-fast WiFi 7 speeds, ensuring enterprise-grade performance in a compact, small business AP.

MLO: Transforming WiFi 7 for Unprecedented Connectivity

Fundamentally, one of the most pioneering advancements of WiFi 7 is the introduction of MLO (Multiple Link Operation). MLO represents a WiFi technology that empowers devices linked to a WiFi access point (AP) to concurrently transmit and/or receive data through various frequency bands and channels. This entails simultaneous connections across the 2.4GHz, 5GHz, and 6GHz bands, a capability absent in earlier WiFi generations where devices were restricted to a solitary WiFi band connection.

The result is a significant amplification in data throughput, a reduction in latency, and an enhancement in reliability. These outcomes undeniably enhance the user experience and unveil novel opportunities for emerging applications such as VR/AR, online gaming, remote office setups, and cloud computing.


RF First by Design

The advanced RF filter design eliminates interference between the 5GHz and 6GHz bands, while the built-in 4G/5G interference filter allows seamless coexistence with 4G/5G cellular networks and minimizes interference, all of which guarantees a seamless WiFi experience without interruptions.

NebulaFlex – simply manage it your way!

NebulaFlex offers extended flexibility, enabling users to effortlessly switch between standalone mode and our intuitive cloud-managed NCC (Nebula Control Center) modes at any time, without incurring additional costs. This ensures adaptability to changing needs while safeguarding investments in wireless technology.

Specifications

Model			NWA50BE
Product name			BE5100 4-Stream WiFi 7 Dual-Radio NebulaFlex Access Point
			
Wireless			
Standard		IEEE802.11 be/ax/ac/n/g/b/a	
MIMO		MU-MIMO	
Wireless speed	2.4GHz	688Mbps	
	5GHz	4324Mbps	
Frequency band	2.4GHz	• USA (FCC): 2.412 to 2.462 GHz • Europe (ETSI): 2.412 to 2.472 GHz	
	5GHz	• USA (FCC): 5.15 to 5.35 GHz; 5.470 to 5.850 GHz • European (ETSI): 5.15 to 5.35 GHz; 5.470 to 5.725 GHz	
Bandwidth		20-, 40-, 80-, 160- and 240-MHz	
Conducted typical transmit output power*1	US (2.4GHz/5GHz)	26/25dBm	
	EU (2.4GHz/5GHz)	20/25dBm	

Model		NWA50BE
RF Design		
Antenna type		Internal Antenna
Antenna gain	2.4GHz	2 dBi, 2x2:2SS
	5GHz	3 dBi, 2x2:2SS
Minimum receive sensitivity		Min. Rx sensitivity up to -99 dBm
WLAN Features		
Band Steering		Yes
WDS/ Mesh*2		Yes
Fast roaming		Pre-authentication, PMK caching and 802.11r/k/v
DCS		Yes
Load balancing		No
Advanced Cellular Coexistence		Yes
Security		
Encryption		WPA/WPA2/WPA3 personal
Authentication		No
Access management		L2-isolation/MAC filtering/Rogue AP detection
Networking		
IPv6		Yes
VLANs		Yes
WMM		Yes
U-APSD		Yes
Management		
Operating mode		Cloud managed / standalone
ZON Utility		• Discovery of Zyxel switches, APs and gateways • Centralized and batch configurations ▪ IP configuration ▪ IP renew ▪ Device reboot ▪ Device locating ▪ Web GUI access ▪ Firmware upgrade ▪ Password configuration
Web UI/CLI		Yes
SNMP		No
Physical Specifications		
Item	Dimensions (WxDxH)(mm/in.)	150 x 150 x 35 / 5.91 x 5.91 x 1.38
	Weight (g/lb.)	412 / 0.91
Packing	Dimensions (WxDxH)(mm/in.)	244 x 168 x 60 / 9.61 x 6.61 x 2.36
	Weight (g/lb.)	785 / 1.73
Included accessories		• Power adapter • Mount plate • Mounting screws
MTBF (hr)		870,551
Physical Interfaces		
Ethernet port		1 x 1/2.5GbE LAN
Power		• Power Adapter: AC100 - 240V - 50/60Hz 0.3A; Output: DC +12V 1.5A • PoE (802.3at): power draw 16W
PoE modes	IEEE 802.3af	Not supported
	IEEE 802.3at	Unrestricted
	IEEE 802.3bt	Unrestricted
Environmental Specifications		
Operating	Temperature	0°C to 50°C/32°F to 122°F
	Humidity	10% to 95% (non-condensing)

Model		NWA50BE
Environmental Specifications		
Storage	Temperature	-40°C to 70°C/-40°F to 158°F
	Humidity	10% to 90% (non-condensing)
Certifications		
Radio	FCC Part 15C, FCC Part 15E,FCC Part 2.1091, ETSI EN 300 328, EN 301 893, Draft EN 303 687, EN 50385, EN 50665, EN IEC 62311, LP0002	
EMC	FCC Part 15B, EN 301 489-1, EN 301 489-17, EN55032, EN55035, EN61000-3-2/-3, EN60601-1-2, BSMI CNS15936	
Safety	EN 62368-1, IEC 62368-1, BSMI CNS15598-1	

*1: Maximum transmit power is limited by local regulatory settings.

*2: WDS, ZyMesh, Smart Mesh and Industry's Open Mesh, Easy Mesh are different mesh systems that do not work with one another.

Recommended Accessories

Mounting Accessory

Model	ACCESSORY-ZZ0105F
Product photo	
Description	BAR ceiling clips for ceiling mount Zyxel AP (5 sets)

For more product information, visit us on the web at www.zyxel.com

Copyright © 2025 Zyxel and/or its affiliates. All rights reserved.
All specifications are subject to change without notice.

